

## 57

## LSM6DSV320X

# For all is on you and around you

## Continue to unleash the potential of our cutting-edge MEMS sensors



### What's the LSM6DSV320X?

New sensor technology for accurate and efficient measurement of both high and low acceleration levels



High-g AXL

A/D

A/D

A/D

MLC

SFLP

Motion

Gyro

Accurate and valuable insights for motion and intense impact tracking

Edge AI and self-configuration: FSM\*, MLC\*, ASC\* and SFLP\* embedded resources

> \*FSM = finite state machine \*MLC = machine learning core \*ASC = adaptive self-configuration \*SFLP = sensor fusion low power

### Which attributes for LSM6DSV320X?





### LSM6DSV320X Differentiating features for new applications

Industry-first high performance 6-axis IMU with a **dedicated high-g accelerometer** for intensity impact and shock detection



Top view of MEMS unit of LSM6DSV320X





### LSM6DSV320X Differentiating features for new applications



Enhanced **contextual awareness** with an IMU embedding AI and advanced processing features









**Emergency calls** 

**Fall/drop reconstruction** 

Intense movements tracking

**Concussion monitoring** 

MLC = machine learning core FSM = finite state machine ASC = adaptive self-configuration SFLP = sensor fusion low power



### You and all around you Applications with LSM6DSV320X



## Now, you can capture all events around you by yourself

#### A comprehensive ecosystem for developers **Software libraries** Software tool **Development kits** Professional MEMS tool Motion XLF (STEVAL-MKI109D) Accuracy data (fusion of high-g and low-g) STEVAL-MKI251A **Sensor fusion** Heterogenous data (different sensors' fusion) SensorTile.Box PRO **Studio Context awareness (MLC)** Human activity recognition, gesture from wrist

Evaluate and program the LSM6DSV320X – Develop embedded AI features, design no-code algorithms



# LSM6DSV320X IMU for you and all around you

#### Innovative structure for optimized low-g and high-g sensing



Dual accelerometer with dedicated channels and self test

- Low-g accelerometer: up to ± 16 g
- High-g accelerometer: up to ±320 g.
- Gyroscope: up to ±4000 dps

#### No overhead in the package size

• Compact IMU footprint: 2.5 x 3.0 x 0.83 mm

#### At-the-edge processing

- Adaptive self-configuration (ASC)
- MLC<sup>(1)</sup> (1 kHz, 256 nodes), FSM<sup>(2)</sup>, SFLP<sup>(3)</sup>
- 1.5 KB FIFO (up to 4.5 KB with compression)
- OIS with Aux I<sup>3</sup>C interface (v1.1)
- And more...



#### Automatic switch with FSM



(1) MLC: Machine learning core
 (2) FSM: Finite state machine
 (3) SFLP: Sensor fusion low power

## Why use LSM6DSV320X?

LSM6DSV320X enables solutions unlocking creativity and transforming applications



- High-g sensing removing false positive detection
- High-fidelity dynamic signal tracking
- Always-on sensing in the best efficient way
- System level complexity reduction and efficiency



## LSM6DSV320X: comparison vs competitors

Features	LSM6DSV320X	Competitor IMUs
Mechanical structure	Three sensing elements in a single package • Gyroscope • Low-g accelerometer (±16 g) • High-g accelerometer (±320 g)	Two sensing elements in a single package • Gyroscope • Low-g accelerometer (±32 g)
Signal dynamics reconstruction	Capable of high-fidelity motion tracking and reconstruction	Limited reconstruction of dynamics
False-positive robustness	High robustness with advanced filtering and signal processing	Basic filtering capabilities
Edge Al	Machine learning core and adaptive self-configuration	
Software libraries	Motion XLF, sensor fusion, context awareness, basic libraries	Basic libraries for standard operations
Target applications	Superior functionality in mobile, IoT, and asset tracking devices	Limited functionality in standard wearable applications



## The perfect product for you and all around you LSM6DSV320X

Industry-first IMU with dual MEMS accelerometer Measures accurately up to 320 g full-scale range

**New frontiers for personal electronics and IoT** Emergency call, drops and falls tracking, concussion, etc

Miniaturized Al-enabled sensor with context-awareness for system level complexity reduction and efficiency

## Our technology starts with You



© STMicroelectronics - All rights reserved. ST logo is a trademark or a registered trademark of STMicroelectronics International NV or its affiliates in the EU and/or other countries. For additional information about ST trademarks, please refer to <u>www.st.com/trademarks</u>. All other product or service names are the property of their respective owners.

